



## Fast Charging Mer Eve

Ideal for workplace, fleet & destination charging.

Three Options Available	Typical Charge Times (60kWh battery)
3.7kW	16-17 hours
7kW	8-9 hours
22kW	3-4 hours



Dual Socket



Clear status indication by full colour display



Can be wall mounted or post mounted



Load balancing available



Access with Plug & Charge or charge card



Personalise with company logo



Cellular and/or Ethernet connected

## Input & Output

Input voltage	230V AC
Input frequency	50Hz
Output voltage	230V 1-phase products 400V 3-phase products
Max output power	7.4 kW 1-phase prod. 22kW 3-phase prod.
Max output current	32A per phase

## Mechanical

Dimensions (H/W/D)	590 x 338 x 230 mm
Weight	15 kg approx

## Work environment

Protection degree	IP54
IK protection	IK10
Stand by consumption	Approx 9 – 12W
Environment temperature	-25C - +40 C

## Function & Accessory

Ethernet/Cellular	Yes/Yes
Communication	OCPP 1.5, 1.6, 2.01
Load management	Yes
Connector	Socket
RFID	Yes

## Mounting Accessories

Wall mounting	Yes
Ground-mounting post	Opt

## Protection/Integrated

Over current protection	Yes (integrated)
Type B RCD	On board
Energy meter	MID certified