



Ultra-rapid charging Alpitronic Hypercharger

Ideal for public charging hubs,
car parks and short stays.

- **Speed:** up to 300kW
- **80% charge** in 10 minutes*

*based on 60kWh battery and
20% starting charge level.



Simultaneous
charging with
dynamic load
balancing



Optional 22kW
AC charging
socket



Futureproof –
scalable and
upgradable
power



15.6-inch
interactive
display



Access with
Charge Card,
App/Driver Portal



Contactless
enabled

Input & Output

Input volume	3x 230 V (400v)
Input frequency	50Hz
Output voltage	150-1000v DC
Max output power	300kW DC
Max output current	CCS2: 500A CHAdeMO: 200A

Work environment

Protection degree	IP54
IK protection	IK10
Stand by consumption	≤ 90w
Environment temperature	-30C to +55C
Protective class	Class I (protective earth connection)

Function & Accessory

Ethernet/Cellular	Yes/Yes
Communication	OCPP 1.6
Load balancing	Yes
Connectors	CCS2, CHAdeMO
RFID	Yes
Contactless	Yes
15.6" display	4 buttons

Mechanical

Dimensions (H/W/D)	2235 x 732 x 663 mm
Weight	375-774 kg (model dependent)
Charging cable lengths	3.5m or 5m