



Rapid charging Delta Slim

Ideal for public car parks and short stays.

- **Speed:** Up to 100kW
- **80% charge** in 30-40 minutes*


*based on 60kWh battery and 20% starting charge level.



Simultaneous charging



Compact design



Dynamic load balancing



7" LCD screen



Access with Charge Card, App/Driver Portal



Contactless enabled

Input & Output

Input voltage	400v AC (+/- 10%)
Input frequency	50/60Hz
Output voltage	200v - 500v
Max output power	CCS - 75kW CHAdeMO - 62.5kW Type 2 - 22kW
Max output current	188A at 400v

Mechanical

Dimensions (H/W/D)	1616 x 892 x 444 mm
Weight	approx. 200kg
Cable length	5.5m
Forced air cooling	yes

Work environment

Protection degree	IP55
IK protection	IK10
Environment temperature	-25C to +50C

Function & Accessory

Ethernet/Cellular	Yes/Yes
Communication	OCPP 1.5, 1.6
Load balancing	Yes
Connectors	CCS, CHAdeMO, Type 2 AC socket
RFID enabled	Yes
Contactless	Yes

Protection

Over current	Yes (integrated)
Over/Under voltage	Yes
Short circuit	Yes
Ground and Isolation monitoring	Yes