



Semi-rapid DC charging Delta Wallbox

Ideal for car parks, workplaces
and destination charging.

- **Speed: 25kW**
- **80% charge in ~ 2 hours***

*based on 60kWh battery and
20% starting charge level.



Cellular and
ethernet network
connectivity



CCS &
CHAdeMO dual
charging ports



Low installation
cost compared
with rapid DC
chargers



Access with
Charge Card,
App/Driver Portal



Wall mount or
optional stand

Input & Output

Input voltage	230v AC; 380-415v AC
Input frequency	50Hz / 60Hz
Output voltage	up to 500v DC
Max output power	25kW
Max output current	60A

Work environment

Ingress protection	IP55
Enclosure protection	IK10
Stand by consumption:	<20W
Operating temperature:	-30C to +50C

Protection

Over current	Yes (integrated)
Over/Under voltage	Yes
Short circuit	Yes
surge protection	Yes
over temperature	Yes
ground fault	Yes

Function & Accessory

Network interface	Ethernet & cellular
Communication	OCPP 1.5S, 1.6J
Connectors	CCS, CHAdeMO
RFID	Yes
2.7" OLED screen	

Mechanical

Dimensions (H/W/D)	4m (standard), 7m (optional for CCS)
Weight	5kg approx.
Charging cable lengths	430 x 680 x 230
Cooling system	Forced air