



Ultra-rapid charging Kempower S Series

Ideal for public charging hubs,
car parks and short stays.

- > **Speed:** up to 200kW
- > **80% charge** in < 20 minutes*

*based on 60kWh battery and
20% starting charge level.



Simultaneous
charging with
dynamic load
balancing



Contactless
payment enabled



Advanced cable
support system



Interactive
touchscreen



Highest power vs
footprint ratio in
market



Access with
charge card, app,
and driver portal

Input & Output

Input voltage	380-400v AC
Input frequency	50-60Hz
Output voltage	400v (standard), 670v (with C800 Series)
Max output power	CCS2 - 200kW CHAdeMO - 100kW
Max output current	CCS2 - 300A CHAdeMO - 250A

Mechanical

Dimensions (H/W/D)	2300 / 420 / 420
Weight	66-172kg (model dependent)
Charging cable lengths	5m or 7m

Work environment

Protection degree	IP54
IK protection	IK10
Standby consumption	- 25W
Environment temperature	-30C to +40C

Function & Accessory

Ethernet & cellular connectivity	Yes
Communication	OCPP 1.6/.20
Load balancing	Yes
RFID & contactless enabled	Yes
Touchscreen	7"
Connectors	CCS2 CHAdeMO

Protection

Over/under voltage	Yes
Surge protection	Yes
Earth leakage current	Yes
Short circuit	Yes
Over temperature	Yes